

Technical specifications

Length overall	15,35 m / 50'4"
Waterline length	14,31 m / 46'1"
Beam	8,10 m / 26'7"
Air draft	23,53 m / 77'2"
Draft	1,40 m / 4′7″
Displacement (CE)	19,91 T / 43,910 Lbs
Upwind sail area (Standard mainsail)	148 m² / 1,592 sq.ft
Upwind sail area (Optional mainsail)	151 m² / 1,625 sq.ft
Full battened mainsail	95 m² / 1,022 sq.ft
Square top mainsail (option)	98 m² / 1,054 sq.ft
Genoa	53 m² / 570 sq.ft
Code 0 (option)	101 m² / 1,087 sq.ft
Fresh water capacity	830 L / 219 US gal
Fuel capacity	1,040 L / 274 US gal
Engines	2 x 80 CV / HP YANMAR
Architects	VPLP Design
Exterior design	Patrick le Quément
Interior design	Nauta Design
Number of berths	8 à 12
CE certification	A:14 - B:14 - C:16 - D:30

North American Specifications

ONLY FOR BOATS SOLD IN US

- 110V electric panel and electric equipment
- US 110V outlets
- Gas propane circuit with solenoid valve

Construction

- Polyester and high quality anti-osmotic resin
- Hull, deck and coachroof laminated by infusion
- Balsa core hull and deck, solid laminated under waterline, white gel coat
- · Laminated or glued plywood

Steering gear

- 2 suspended rudder blades
- Hydraulic steering transmission
- Emergency tiller

Sails and rigging

SAILS

- High roach mainsail in Dacron with battens
- Genoa in Dacron with UV protective band

STANDING RIGGING

- · Anodized aluminium mast on the roof
- Anodized aluminium boom
- · 2 spreaders rigs
- Coated shrouds
- Furling forestay for self-tacking jib
- 2 forestay chainplates and 1 shroud chainplates
- Ajustable lazy-jacks

RUNNING RIGGING

- · Mainsail halyard
- · Genoa halyard
- Mainsheet
- · 2 genoa sheets
- 3 reefing lines
- · Genoa furling line
- Mainsheet traveler lines
- Boom uphaul
- Mainsheet fuse

Hardware

- 3 manual winches size 50.2 STA
- Footblocks & clutches for halyards, reefing lines and sheets
- · Mainsail track and ball-bearing car
- 2 genoa sheet tracks
- Anodized aluminium crossbeam with fixing point for the genoa furler, and anchor roller

Mooring

- Composite longitudinal crossbeam with integrated chain run and mooring cleat
- 8 mooring cleats
- 2000W / 12V electrical windlass with vertical axis, chain 12 mm

Engines

- 2 diesel engines YANMAR 4JH80 80CV SailDrive
- Fixed three blade propeller
- Sea water filter
- Mechanical engine throttles at the helm station
- Engine compartment ventilation: 12V electrical extraction in the aft transom
- Fuel circuit:
 - 2 rotomoulded tanks of 520L / 137 US gal
 - Fuel filter systems
 - Fuel shut off valve
 - Gauge at the general control panel on touch screen

Plumbing

FRESH WATER CIRCUIT

- Fresh water tank: 830L / 219 US gal with gauge at the chart table
- Fresh water circuit with 1 main water group 36L/mn
- Hot water circuit with 60L / 16 US gal water heater and engine exchanger

GREY WATER CIRCUIT

- Shower and sink draining by automatic water sensor with timer
- Grey water drainage cockpit and salon direct to the sea

BLACK WATER CIRCUIT

- Black water holding tanks:
 - 4-cabin, 3 heads version: 240L / 63 US gal
 - 4-cabin, 4 heads version: 310L / 82 US gal
 - 6-cabin, 4 heads version: 310L / 82 US gal
- · Tank drain by gravity or deck plate

BILGE PUMP CIRCUIT

- 1 manual bilge pump per hull
- 1 automatic immersed bilge pump per hull, with alarm signal
- 1 float swith per sump
- Self-draining cockpit compliant to the CE certifications

Electrical

 Seanapps® connectivity - Battery voltage and GPS position on mobile app

DC POWER CIRCUIT - 12V

- 2 harnessed alternators 125A
- 2 engine batteries 50A (AGM)
- 3 service batteries 140A (AGM)
- Battery circuit breakers in the engine compartments

DISTRIBUTION ELECTRIC PANEL

- General control panel 12V at chart table
- USB sockets 12V included in the electrical panel
- 2 USB sockets 12V at the helm station

220v ac circuit

Inverter 24/220V 50Hz 1200VA

LIGHTING

- 12V LED interior lighting and reading lights
- 12V lighting in engine compartment
- · LED navigation lights
- Deck light on mast

Deck layout

TRANSOM

- · Hot/cold deck shower on starboard
- S/S telescopic swim ladder with fixed handles on starboard

AFT COCKPIT

- · L-shaped bench on port side
- Gas locker
- Polyester cockpit table
- Exterior furniture on starboard:
 - Corian® countertop
 - Integrated sink
 - Tray and cup holder
 - Double door with shelves
- Lounger with locker to starboard
- Composite aft beam:
 - Seats
 - Liferaft locker under seat
- Cockpit flush-decked with saloon
- · Composite non-streaming toe rails on cockpit sides
- Non-slip cockpit floor
- Self-draining cockpit with wooden grating

FLYBRIDGE

- Access from the cockpit and deck
- Double helm seat
- C-shaped seats aft of the helm station
- Leather covered steering wheel ø900mm
- Engine throttles and panel
- Console for screen and instrumentation
- Storage bag for halyards

FORWARD COCKPIT

- U-shaped seating area
- Large hatches for technical access
- Nylon netting

BOW LOCKERS

- Access through LEWMAR T60 deck hatches
- Wooden floor
- · LED lighting

STANCHIONS AND LIFELINES

- Pushpits: H610 mm / 24in
- 10 stanchions: H610 mm / 24in
- Double S/S lifelines

Interior layouts

GENERAL

- Construction in Alpi Sand Oak plywood, horizontal grain
- Laminated floor: Dark Oak
- 100% recycled upholstery, adapted to the marine environment
- Ceiling and hull linings in padded PVC foam
- Eco-Cleaning Pack
- Furniture interiors in Okoumé finish

GALLEY

- Corian® countertop
- Port side:
 - U-shaped galley
 - Large s/s sink with Corian® cover
 - Hot/cold mixer tap
 - 4-burner gas stove
 - Gas oven
 - Bin
- Starboard:
 - 12V 190L / 50 US gal refrigerator
- High and low storages with shelves, drawers and bottle rack

SALON

- · L-shaped sofa
- Wooden dining table
- Chart table on starboard
- Central furniture:
 - Seat with backrest
 - Bottles storage

OWNER'S CABIN

- Double bed with lateral access (2,00 x 1,60 m / 6'7" x 5'3")
- Treated cellular foam mattress
- Under bed storage
- Walk-in dressing with sliding door
- Storage units with shelves, drawers and wardrobe
- Sofa
- Desk with 1 stool
- T44 and T10 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening portholes and roller blind

OWNER'S HEAD

- Private access from the Owner's cabin
- Corian® countertop
- Integrated sink with hot/cold mixer tap
- · High and low-level storage units
- Separated shower with PMMA door
- · Separated toilets with storages
- T44 and T10 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening porthole

AFT CABINS

- Double bed with lateral access (2,00 \times 1,60 m / 6'7" \times 5'3")
- Treated cellular foam mattress
- Under bed storage
- Meubles de rangement avec étagères, tiroirs et penderies
- T44 opening flush deck hatch
- Fixed hull window in PMMA with integrated opening porthole and roller blind

LATERAL CABIN

- Bed with lateral access (2,00 x 1,60 m / 6'7" x 5'3")
- · Treated cellular foam mattress
- · Full height unit with shelves and wardrobe, and storage units
- Sliding hatch on salon with blackout blind

FORWARD CABIN

- Bed with lateral access (2,00 x 1,60 m / 6'7" x 5'3")
- Treated cellular foam mattress
- Under bed storage
- Full height unit with shelves and wardrobe
- T44 opening flush deck hatch
- Fixed hull window in PMMA with integrated opening porthole and roller blind

HEADS

- · Corian® countertop
- Integrated sink with hot/cold mixer tap
- High and low-level storage units
- Separated shower with PMMA door
- Manual toilet
- T10 opening flush deck hatch
- Fixed hull window in PMMA



162, quai de Brazza CS 81217 33072 Bordeaux Cedex - France Tél. 33 + (0) 557 80 92 80 E-mail : info@cata-lagoon.com

www.cata-lagoon.com