



## Technical specifications

Length overall	16,56 m / 54'4"
Waterline length	16,39 m / 53'9"
Beam	9,00 m / 29'6"
Air draft	28,93 m / 94'11"
Draft	1,55 m / 5'1"
Displacement (CE)	27,7 T / 61,079 Lbs
Upwind sail area (Standard mainsail)	177 m <sup>2</sup> / 1.905 sq.ft
Upwind sail area (Optional mainsail)	183 m <sup>2</sup> / 1.969 sq.ft
Full battened mainsail	103 m <sup>2</sup> / 1.108 sq.ft
Square top mainsail (option)	109 m <sup>2</sup> / 1.173 sq.ft
Self-tacking jib	74 m <sup>2</sup> / 796 sq.ft
Code 0 (option)	154 m <sup>2</sup> / 1.657 sq.ft
Fresh water capacity	960 L / 254 US gal
Fuel capacity	1,100 L / 291 US gal
Engines	2 x 80 CV / HP YANMAR
Architects	VPLP Design
Exterior design	Patrick le Quément
Interior design	Nauta Design
Number of berths	8 à 12
CE certification	A : 14 - B : 14 - C : 16 - D : 30

## North American Specifications

---

### ONLY FOR BOATS SOLD IN US

- 110V electric panel and electric equipment
- US 110V outlets
- Gas propane circuit with solenoid valve

## Construction

---

- Polyester and high quality anti-osmotic resin
- Hull, deck and coachroof laminated by infusion
- Balsa core hull and deck, solid laminated under waterline, white gel coat
- Laminated or glued plywood

## Steering gear

---

- 2 suspended rudder blades
- Hydraulic steering transmission
- Emergency tiller

## Sails and rigging

---

### SAILS

- High roach mainsail in Dacron with battens
- Self-tacking jib in Dacron with UV protective band

### STANDING RIGGING

- Anodized aluminium mast on the roof
- Anodized aluminium boom
- 2 spreaders rigs
- Coated shrouds
- Furling forestay for self-tacking jib
- 2 forestay chainplates and 1 shroud chainplates
- Adjustable lazy-jacks

### RUNNING RIGGING

- Mainsail halyard
- Self-tacking jib halyard
- Mainsheet
- Self-tacking jib sheet
- 2 automatic reefing lines (R1 and R2)
- Traditional 3rd reef (with strap)
- Self-tacking jib furling line
- Mainsheet traveler lines
- Boom uphaul
- Mainsheet fuse

## Hardware

---

- 2 manual winches size 60.2 STA
- 1 manual winch size 50.2 STA
- Footblocks & clutches for halyards, reefing lines and sheets
- Mainsail track and ball-bearing car
- Track and car for self-tacking jib sheet with stopper
- Anodized aluminium crossbeam with fixing point for the self-tacking jib furler, and anchor roller

## Mooring

---

- Composite longitudinal crossbeam with integrated chain run and mooring cleat
- 8 mooring cleats
- 2000W / 24V electrical windlass with vertical axis, chain 12 mm

## Engines

---

- 2 diesel engines YANMAR 4JH80 80CV SailDrive
- Fixed three blade propeller
- Sea water filter
- Mechanical engine throttles at the helm station
- Engine compartment ventilation: 24V electrical extraction in the aft transom
- Fuel circuit:
  - 2 aluminium tanks of 550L / 145 US gal
  - Fuel filter systems
  - Fuel shut off valve
  - Gauge at the general control panel on touch screen

## Plumbing

---

### FRESH WATER CIRCUIT

- Fresh water tank: 960L / 254 US gal with gauge at the chart table
- Fresh water circuit with 1 main water group 36L/mn
- 4 and 5-cabin version: 60L / 16 US gal water heater, 220V engine exchanger
- 6-cabin version: 100L / 26 US gal water heater, 220V engine exchanger

### GREY WATER CIRCUIT

- Grey water drainage cockpit and salon direct to the sea
- Shower and sink draining by automatic water sensor with timer.

### BLACK WATER CIRCUIT

- Black water holding tanks:
  - 4-cabin version: 304L / 80 US gal
  - 5-cabin version: 374L / 99 US gal
  - 6-cabin version: 456L / 120 US gal
- Tank drain by gravity or deck plate

### BILGE PUMP CIRCUIT

- 1 manual bilge pump per hull
- 1 automatic and electric bilge pump in each engine compartment
- Connection of the engine compartments and forepeaks to the main pump and sump
- Bilge pump management on general control panel
- Self-draining cockpit compliant with CE certification

## Electrical

---

- Seanapps® connectivity - Battery voltage and GPS position on mobile app

### DC POWER CIRCUIT - 12V

- 2 engine batteries 50A (AGM)
  - 2 harnessed alternator 60A
  - Battery shutoff switch in each engine compartment
- 6 service batteries 140A (AGM)
  - 2 harnessed alternator 140A
  - Battery shutoff switch in the front technical compartment

### ELECTRIC DISTRIBUTION PANELS

- 24V general distribution panel
- USB sockets 24V included in the electrical panel and helm station

### 220V AC CIRCUIT

- Inverter 24/220V 50Hz 1200VA

### LIGHTING

- LED interior lighting and reading lights
- 12V lighting in engine compartment
- LED navigation lights

## Deck layout

---

### TRANSOM

- Hot/cold deck shower on starboard
- S/S telescopic swim ladder with fixed handles on starboard

### AFT COCKPIT

- U-shaped bench
- Gas locker
- Polyester cockpit table
- Exterior furniture on port side
  - Integrated sink
  - Chopping board
  - Tray and cup holder
  - Double door with shelves
- Lounger with storage locker to port
- Cockpit flush-decked with saloon
- Composite non-streaming toe rails on cockpit sides
- Non-slip cockpit floor
- Self-draining cockpit with wooden grating

### FLYBRIDGE

- Stairway access from cockpit on port side
- Double helm seat
- L-shaped bench seat with storage locker
- Sunbathing areas aft and forward of the bench seat
- Leather covered steering wheel ø900mm
- Engine throttles and panel
- Console for screen and instrumentation
- Storage bag for halyards

### FORWARD COCKPIT

- U-shaped seating area
- Large hatches for technical access
- Nylon netting

### BOW LOCKERS

- Access through LEWMAR T60 deck hatches
- Grey non-slip floor
- LED lighting

### STANCHIONS AND LIFELINES

- Pushpits: H715 mm / 2'4"
- 10 stanchions: H700 mm / 2'3"
- Double S/S lifelines

## Interior layouts

---

### GENERAL

- Construction in Alpi Sand Oak plywood, horizontal grain
- Laminated floor: Dark Oak
- 100% recycled upholstery, adapted to the marine environment
- Ceiling and hull linings in padded PVC foam
- Eco-Cleaning Pack
- Furniture interiors in Okoumé finish

### GALLEY

- Starboard:
  - L-shaped galley
  - Corian® countertop
  - S/s sink with Corian® cover
  - Hot/cold mixer tap
  - 4-burner gas stove
  - Gas oven
  - 50L bin
- Portside (6-cabin version only):
  - 220V 311L / refrigerator

### SALON

- U-shaped sofa
- Wooden dining table
- Chart table and 1 stool on port side
- Bookshelf forward and under seats and floor storages

### OWNER'S CABIN

- Double bed with lateral access (2,00 x 1,70 m / 6'7" x 5'7")
- Treated cellular foam mattress
- Under bed storage
- Storage units with shelves, drawers and wardrobe
- Sofa
- Desk with 1 stool
- T44 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening portholes and roller blinds

### OWNER'S HEAD

- Private access from the Owner's cabin
- Corian® countertop
- Integrated sink with hot/cold mixer tap
- High and low-level storage units
- Separated shower with PMMA door
- Separated toilets with storages
- T44 and T10 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening porthole and roller blinds

### AFT CABINS

- Double bed with lateral access (2,00 x 1,70 m / 6'7" x 5'7")
- Treated cellular foam mattress
- Under bed storage
- Storage units with shelves, drawers and wardrobe
- 5 and 6-cabin version: direct access from the aft cockpit
- T44 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening portholes and roller blind

### CENTRAL PASSAGEWAY - 4-CABIN VERSION

- Fridge & freezer: 220V 311L / 82 US gal
- Storage unit with shelves and wardrobe
- T10 opening flush deck hatch

### LATERAL CABIN - VERSION 5 & 6-CABIN VERSION

- Bed with lateral access (2,00 x 0,80 m / 6'7" x 2'7")
- Treated cellular foam mattress
- Under bed storage
- Full height unit with shelves and wardrobe, and storage units
- T44 opening flush deck hatches

### FORWARD CABIN

- Double bed with lateral access (2,00 x 1,70 m / 6'7" x 5'7")
- Treated cellular foam mattress
- Bedside shelves
- Under bed storage
- Storage units with shelves, drawers and wardrobe
- T44 opening flush deck hatches
- Fixed hull window in PMMA with integrated opening portholes and roller blind

### HEADS

- Corian® countertop
- Integrated sink with hot / cold mixer tap
- High and low-level storage units
- Separated shower with PMMA door
- Manual toilet
- T10 opening flush deck hatch
- Fixed hull window in PMMA



162, quai de Brazza CS 81217  
33072 Bordeaux Cedex - France  
Tél. 33 + (0) 557 80 92 80  
E-mail : [info@cata-lagoon.com](mailto:info@cata-lagoon.com)  
[www.cata-lagoon.com](http://www.cata-lagoon.com)